


Disk Drive Power Connection System


50801TF Series Crimp Terminal

- For use with AWG #16-#22 wire
- Used in 50801HM-N housings
- Tin plated brass or phosphor bronze

50801TF1 One lance



50801TF2 Two lance



Dimensions & Ordering Information:

Part No	Dimension (mm)				Wire		Terminal			Note	Q'ty/Reel
	a	b	c	d	Accommodation (# AWG)	Insulation (O.D. MAX)	Thickness (mm)	Material	Finish		
50801TF1	2.3	2.5	3.3	4.2	#22 - #18	φ 2.2mm	0.3	Brass	Tin-plated	One lance	7,000
50801TF2-1	2.4	2.3	3.4	4.0							
50801TF2P-1	3.3	3.4	3.5	4.8	#20 - #16	φ 2.5mm		Phosphor bronze		Two lances	
50801TF2-2											
50801TF2P-2								Phosphor bronze			

50801HM-N Series Crimp Terminal Housing

- 2-4 circuits available
- UL 94V-2 nylon 66, nature color
- Accepts 50801TF terminal
- Mates with 50801HF-N housing
- Mates with 50801W -N header

Dimensional Information -in (mm)

Circuits	Dim. A	Dim. B
2	0.200 (5.08)	0.427 (10.84)
3	0.400 (10.16)	0.827 (15.92)
4	0.600 (15.24)	0.827 (21.00)

